

N9463D CESSNA 172RG

<u>PWA</u>	<u>FREQUENCIES</u>	<u>PWA TRAFFIC</u>	<u>PATTERN ALTITUDES</u>
ATIS	128.72	17L/35 R	2300 MSL
GROUND	121.7	17R/35 L	1900 MSL
TOWER (7:00AM - 10:00PM)	126.9		
CTAF (10:01PM - 6:59AM)	126.9	FUEL GRADE	
APPROACH	124.6	100 LL (BLUE)	
VOR	113.4	USABLE FUEL - 62 GAL. MAXIMUM	
		44 GAL. REDUCED TO TABS.	

ITEM	WEIGHT	XARM=	MOMENT
	(LBS.)	(INCHES)	
EMPTY WEIGHT	1,680.10	38.34	64,411.12
USABLE FUEL		48	
PILOT & FRONT PASS.		37	
REAR PASS.		73	
BAGGAGE 1		95	
BAGGAGE 2		115	
RAMP WT/MOM.			
ENGINE START, TAXI, AND RUNUP	-8	48	-384
TAKEOFF WT. & MOM.			
CG = MOMENT/WT.			

USEFUL LOAD 977.9 POUNDS

USEFUL LOAD WITH 44 GAL. (TABS) IS 713.9 LBS.

USEFUL LOAD WITH 62 GAL. (FULL FUEL) IS 605.9 POUNDS

BAGGAGE COMPARTMENT MAXIMUM ALLOWANCE COMBINED WEIGHT CAPACITY = 200 LBS.

AIRCRAFT MAXIMUM ALLOWANCE GROSS WEIGHT = 2650 LBS.

AIR SPEED

VNE	164
VNO	145
VA	106
VS	50
VSO	42
Vx	67
Vy	84
MAX GLIDE (FLAPS 0 DEGREE)	70
VLO GEAR OPERATING	140
VFE FLAPS 10 DEGREES <2,550 LBS.	130
FLAPS 10-30 DEGREES	100

KIAS

164
145
106
50
42
67
84
70
140
130
100

ATIS WEATHER

ATIS ID	
WIND	
VISIBILITY	
CEILING	
TEMP.	
DEWPOINT	
ALTIMETER	
RUNWAY	
INFO.	